



DRYING

Tullis

SINGLE POCKET DRYERS

S-330 /S-440 /S-550 /S-660 /S-900 /S-1200 /S-1500



CHARACTERISTICS

TP2

- User friendly and totally programmable 7" TP2 touch screen
- USB Connection. PC software free of charge for programming, traceability, data analysis...
- Videos on display (ads, instructions)
- 37 languages
- iDRY - Intelligent humidity control with new drum inlet temperature control.
 - Standard on models S-900 to S-1500.
 - Optional extra on models S-330 to S-600.

OUTSTANDING FEATURES

- Reversing drum action as standard
- Stainless steel drum as standard
- Frequency inverter as standard

EFFICIENCY

- MIXED FLOW - New 'optimized' system of mixed airflow
- Big fluff filter

VERSATILITY

- Make to order - customisation
- WET CLEANING
- OPL > Multivending - Standard OPL model easily transformable to coin laundry uses or to mobile cashless payment system

ERGONOMICS

- Drawer as fluff filter, made of stainless steel
- Biggest door diameters
- Opening sense of door adjustable on site

MAINTENANCE

- Hinged panel: easy and ergonomic access
- Technical menu: statistics, alarm, autotest, data recovery for technicians and maintenance

OTHERS

- Grey skinplate outer casing, stainless steel look
- SOFT TOUCH - new drum with stamped holes
- COOL DOWN - anti-wrinkle at the end of the cycle
- Heating options: electric, gas and steam
- CE approved

CONNECTIVITY

- Remote technical service
- Management of laundries: OPL and COIN
- Remote payment:
Laundry
CONNECT

TECHNICAL DATA

SINGLE POCKET DRYERS | S-330 / S-440 / S-550 / S-660 / S-900 / S-1200 / S-1500

	UNIT	S-330	S-440	S-550	S-660	S-900	S-1200	S-1500
CAPACITY								
Capacity 1:20	kg	16,5	22	27,5	33	45	60	75
Capacity 1:18	kg	18,3	24,3	30,6	36,7	50	66,7	83,3
Hourly output	kg	28.3 to 32.6	40	59.3	60 to 63.9	80.4 to 84.4	120 to 128.6	128.6 to 173.1
Evaporation capacity	l/min	14.1	20	30.9	31.1 to 32.1	40,2	60.2	64 to 86.5
DRUM								
Ø Drum	mm	750	835	947	947	1225	1225	1225
Ø Door	mm	574	574	802	802	802	802	802
Door centre height	mm	976	1030	1040	1,040	1,275	1,275	1,275
Load hole bottom height	mm	689	743	640	640	874	874	874
Drum length	mm	746	800	780	936	760	1,020	1,252
Drum volume	l	330	438	549	660	896	1,202	1,500
POWER								
Drum motor power	kW	0,37	0,37	0,55	0,55	0,75	1,1	1,5
Fan motor power	kW	0,25	0,55	0,55	0,55	1,1	1,1	1,1
Electric heating power	kW	18	24	30	36	54	72	72
Total electric power	kW	18,67	24,97	31,15	37,15	55,9	74,25	74,65
CONNECTIONS								
Ø Gas inlet	mm	12,7	12,7	12,7	12,7	19	19	19
Ø Steam inlet	mm	160 / 101	25,4	25,4	25,4	25,4	25,4	25,4
Ø Condensed (Steam models)	mm	76 / 101	25,4	25,4	25,4	25,4	25,4	25,4
DIMENSIONS / PACKAGING DIMENSIONS								
Net width / Gross width	mm	785 / 865	890 / 970	985 / 1065	985 / 1065	1270 / 1330	1270 / 1330	1270 / 1330
Net depth / Gross depth	mm	1125 / 1210	1255 / 1345	1054 / 1154	1210 / 1310	1106 / 1185	1366 / 1445	1598 / 1705
Net height / Gross height	mm	1694 / 1840	1812 / 1940	1975 / 2080	1975 / 2080	2380 / 2150	2380 / 2150	2380 / 2150
Height without heating battery	mm	-	-	-	-	-	-	-
Net weight / Gross weight	kg	187 / 200	210 / 230	230 / 260	260 / 285	395 / 430	529 / 575	657 / 715
OTHERS								
Max airflow	m3/h	850	1.200	1.200	1.200	3.000	3.000	3.000
Ø Fume exhaust	mm	200	200	200	200	300	300	300
Sound level	dB	64	65	65	65	67	67	67

